



* PER PENNDOT
BUT NOT LESS THAN
SHOWN ON PLANS

COMMENTS:

1. EXPOSED VERTICAL AND HORIZONTAL SURFACES SHALL BE PREPARED AS PER PUB. 408, SECTION 413.3(g).
2. MINIMUM 1' PAVEMENT CUTBACK, EXCAVATE OLD AND TEMPORARY MATERIAL. RECOMPACT SUB-GRADE. TACK COAT ALL VERTICAL EDGES. INSTALL ONLY BASE COURSE AND BINDER COURSE IN ONE DAY, OR AS DIRECTED.
3. PERMANENT RESTORATION TO BE MINIMUM 90 DAYS UNLESS FLOWABLE FILL IS USED, OR AS DIRECTED.

NOTE:

1. MATCH EXISTING DEPTHS IF GREATER.
2. RESTORE PAVEMENT MARKINGS WITH APPROVED THERMOPLASTIC PAINT.

PENNDOT FLEXIBLE TRENCH RESTORATION

NOT TO SCALE

REVISED 7/20/22

FLEXIBLE PAVEMENT RESTORATION

PREPARED FOR:

PERKASIE REGIONAL AUTHORITY

ANDERSEN
ENGINEERING
ASSOCIATES
INCORPORATED
150 RIDGE ROAD, SUITE 2, SELLERSVILLE, PA 18960
(215) 257-5711

DSN BY: P.C.A.

CHK BY: P.C.A.

DATE: 5/21/12

DWG NO. PRA-S022B